


## Kompaktfilter RELIM VRK 85

### Description

- RELIM Compact Air Filter from stable, multi-sided sealed filter plates
- closely pleated filter media made of synthetic multi-layer micro spunbond
- KALTHOFF INTERMELT-pleating system for low resistance performance
- strong KALTHOFF casing from full plastic
- suitable for high airflows



### Types


Article	VRK 85-6	VRK 85-5	VRK 85-3
Front size (WxH)	592x592 mm	592x490 mm	592x287 mm
Depth of cartridge (D)	292 mm	292 mm	292 mm
Filtering surface	13,3 m <sup>2</sup>	11,0 m <sup>2</sup>	6,6 m <sup>2</sup>
Nominal airflow (100-125%)	4250-5300 m <sup>3</sup> /h	3500-4400 m <sup>3</sup> /h	2100-2600 m <sup>3</sup> /h

### Technical Data

Filter class:	DIN EN 779	F7
Filter group:	DIN ISO 16890	ISO ePM1 55%
Efficiency:	ePM1	59%
<b>Pressure drop at 100% nominal airflow</b>		
initial:	Pa	115
final (recommended):	Pa	300
Max. operation temperature:	°C	80
Max. operation moisture (rel. humidity):	%	100
Classification of inflammability:	DIN EN 13501	E

Technical data are being compiled to the best of our knowledge. Responsibility cannot be accepted. We reserve the right of technical modifications. Version 1/19

### Pressure Drop



Ihr Partner für Filtertechnik

