

## Kanalfiltergehäuse

### Description

- 30 mm air duct flanges connecting duct to upstream and downstream side
- user-friendly lateral maintenance door with star grips for tool-free filter changing, optional in right or left air direction
- universal installation frame with four friction springs for filters up to design height of 48 mm, laterally pushed in casing
- spot-welded, stamped support grids, without sealing



### Application

Duct filter casing with small upstream profile for installation in filter air ducts

### Material

Solid duct filter casing from sheet steel material, galvanized or stainless steel 1.4301

### Duct filter – single step

Type	01	02	03	04	05	06	07	08	09	10
Number Filter units	21	2	3	4	5	6	7	8	9	10
height in mm H	280	500	720	940	1.160	1.380	1.600	1.820	2.040	2.260
width in mm W	670	670	670	670	670	670	670	670	670	670
approx. weight kg/unit, galvanized	20	30	39	48	57	66	76	85	95	104

### Duct filter – double step

Type	01/01	02/02	03/03	04/04	05/05	06/06	07/07	08/08	09/09	10/10
Anzahl Filterelemente	2	4	6	8	10	12	14	16	18	20
Höhe in mm H	280	500	720	940	1.160	1.380	1.600	1.820	2.040	2.260
Breite in mm B	1.280	1.280	1.280	1.280	1.280	1.280	1.280	1.280	1.280	1.280
Gewicht ca. kg St., vz.	38	58	76	94	102	130	150	168	188	206

Technical data are being compiled to the best of our knowledge. Responsibility cannot be accepted. We reserve the right of technical modifications.  
Version 6/14